

DT-1136P, DT-1128P

Built with side pressure plate for fast, accurate positioning.

- Maximum diameter of cut
DT-1136P: Ø36"
DT-1128P: Ø28"
- Single table
- Single cutterhead
- With side pressure plate



SPECIFICATIONS:

MODEL	DT-1136P	DT-1128P
Range of cutting diameter	4"-30"	3"-22"
Maximum rectangular cutting (2:1)	26.8" X 13.4"	19.6" X 9.8"
Table diameter	26"	18"
Table rotation speed (Auto variable)	1.5-4 RPM	1.5-4 RPM
Spindle speed	8000 RPM	8000 RPM
Spindle diameter	1", 30 mm, 1-1/4"	1", 30 mm, 1-1/4"
Cutter size	100 mm	100 mm
Follower roller diameter	100 mm	100 mm
Table drive motor	1 HP x 1	1 HP x 1
Spindle drive motor	7-1/2 HP x 1	7-1/2 HP x 1
Net weight	950 kgs	830 kgs
Gross weight	1240 kgs	1060 kgs
Packing size	81" x 74" x 77"	68" x 64" x 77"

All specifications, dimensions and design characteristics shown in this catalogue are subject to change without notice.



SIDE PRESSURE PLATE

A side pressure plate can be supplied as optional equipment to provide secure positioning of the workpiece. The side pressure plate can be built on the standard cutterhead models.