

# DT-1236N, DT-1228N, DT-1136N, DT-1128N

More safety of full splash guard design



- Maximum diameter of cut  
DT-1236N: Ø36" DT-1136N: Ø36"  
DT-1228N: Ø28" DT-1128N: Ø28"
- Single table
- Single cutterhead or Double cutterhead

## SPECIFICATIONS:

| MODEL                                | DT-1236N          | DT-1136N          | DT-1228N          | DT-1128N          |
|--------------------------------------|-------------------|-------------------|-------------------|-------------------|
| Range of cutting diameter            | 4"-36"            | 4"-36"            | 3"-28"            | 3"-28"            |
| Maximum rectangular cutting (2:1)    | 32" X16"          | 32" X16"          | 25" X12.5"        | 25" X12.5"        |
| Table diameter                       | 26"               | 26"               | 18"               | 18"               |
| Table rotation speed (Auto variable) | 1.5-4 RPM         | 1.5-4 RPM         | 1.5-4 RPM         | 1.5-4 RPM         |
| Spindle speed                        | 8000 RPM          | 8000 RPM          | 8000 RPM          | 8000 RPM          |
| Spindle diameter                     | 1", 30 mm, 1-1/4" | 1", 30 mm, 1-1/4" | 1", 30 mm, 1-1/4" | 1", 30 mm, 1-1/4" |
| Cutter size                          | 100 mm            | 100 mm            | 100 mm            | 100 mm            |
| Follower roller diameter             | 100 mm            | 100 mm            | 100 mm            | 100 mm            |
| Table drive motor                    | 1 HP x 1          | 1 HP x 1          | 1 HP x 1          | 1 HP x 1          |
| Spindle drive motor                  | 7-1/2 HP x 2      | 7-1/2 HP x 1      | 7-1/2 HP x 2      | 7-1/2 HP x 1      |
| Net weight                           | 1250 kgs          | 1050 kgs          | 1120 kgs          | 940 kgs           |
| Gross weight                         | 1500 kgs          | 1300 kgs          | 1320 kgs          | 1140 kgs          |
| Packing size                         | 91" x 77" x 90"   | 91" x 77" x 90"   | 83" x 65" x 90"   | 83" x 65" x 90"   |

All specifications, dimensions and design characteristics shown in this catalogue are subject to change without notice.



## AUTOMATIC TABLE SPEED VARIATION

This allows the feed rate to be adjusted according to the stock thickness and component shape, to give optimum output.