

DT-1172, DT-1162

Continuous multi-station working...
High production capability!



- Maximum diameter of cut
DT-1172: Ø72"
DT-1162: Ø62"
- Single table
- Single cutterhead

SPECIFICATIONS:

MODEL	DT-1172	DT-1162
Range of cutting diameter	10"-72"	10"-62"
Maximum rectangular cutting (2:1)	64.2" x 32.1"	55.2" x 27.6"
Table diameter	46"	46"
Table rotation speed (Auto variable)	1-3 RPM	1-3 RPM
Spindle speed	9000 RPM	9000 RPM
Spindle diameter (Interchangeable)	1", 30 mm, 1-1/4" (One dia furnished)	1", 30 mm, 1-1/4" (One dia furnished)
Cutter size	100 mm	100 mm
Follower roller diameter	100 mm	100 mm
Table drive motor	2 HP x 1	2 HP x 1
Spindle drive motor	10 HP x 1	10 HP x 1
Net weight	1450 kgs	1350 kgs
Gross weight	1900 kgs	1770 kgs
Packing size	86" x 75" x 81"	73" x 66" x 80"

All specifications, dimensions and design characteristics shown in this catalogue are subject to change without notice.



VARIABLE TABLE DRIVE

The infinitely variable table speed permits operations at a wide range of speeds. This allows the feed rate to be adjusted according to the stock thickness and component shape, to give optimum output.