

DT-1236, DT-1228

Economical model series




- Maximum diameter of cut
DT-1236: Ø36"
DT-1228: Ø28"
- Single table
- Double cutterhead



SPECIFICATIONS:

MODEL	DT-1236	DT-1228
Range of cutting diameter	4"-36"	3"-28"
Maximum rectangular cutting (2:1)	32" x 16"	25" x 12.5"
Table diameter	26"	18"
Table rotation speed (Auto variable)	1.5-4 RPM	1.5-4 RPM
Spindle speed	8000 RPM	8000 RPM
Spindle diameter	1", 30 mm, 1-1/4"	1", 30 mm, 1-1/4"
Cutter size	100 mm	100 mm
Follower roller diameter	100 mm	100 mm
Table drive motor	1 HP x 1	1 HP x 1
Spindle drive motor	7-1/2 HP x 2	7-1/2 HP x 2
Net weight	1070 kgs	960 kgs
Gross weight	1390 kgs	1190 kgs
Packing size	73" x 64" x 80"	66" x 58" x 78"

All specifications, dimensions and design characteristics shown in this catalogue are subject to change without notice.



AUTOMATIC TABLE SPEED VARIATION

This allows the feed rate to be adjusted according to the stock thickness and component shape, to give optimum output.